

Offshore 20-foot Cargo

Uniteam deliver 20' containers for offshore usage. The container is produced in accordance with the DNV Certification Notes 2.7-1 and NS-EN 12079.



Offshore 20' unit.

It is the primary construction frame which is tested and certified. This means that the container is tested and certified with out wall, roof and door. This makes the container easily adjustable without new certification.

Uniteam also deliver off shore certified containers ready fitted for storage, workshop, control room etc. with windows and doors. The containers can also be delivered with fire protection (A60 – H120), ex protection, gas detection and as a gas safe shelter. All in compliance with NORSOK Z-015.



Surface treatment for a highly corrosive environment
Sand blasted SA 2.5 in accordance with ISO 8501-1

External:

Hempadur Zink 1536 - 40 µm TFT
Hempadur 1557 - 80 µm TFT
Hempatex Hi-Build 4641, RAL 5010 - 80 µm TFT

Internal:

Hempadur Zink 1536 - 40 µm TFT
Hempadur 1557 - 50 µm TFT Hempatex
Hi-Build 4641, RAL 7035 - 80 µm TFT

Technical Specification:

External	Length	6058 mm
	Width	2438 mm
	Height	2969 mm
Internal	Length	5902 mm
	Width	2328 mm
	Height	2500 mm
Door opening	Width	2328 mm
	Height	2500 mm
Tara Weight		4650 kg
Max total Weight allowed		19 600 kg